

MG Red Shift 5W30 C3 Super Combo



APPLICATION

A modern engine oil manufactured using synthetic technology. The unique formulation creates an ultra-thin protective film on metal surfaces, providing maximum protection against wear and corrosion. The advanced technology significantly reduces friction and operating resistance, resulting in improved engine performance and lower operating costs through reduced fuel consumption. The oil formulation and manufacturing process comply with strict quality standards, ensuring reliable engine operation in both summer and winter conditions, during city driving as well as highway use. It helps reduce harmful emissions released into the environment. Compatible and mixable with other high-quality engine oils of the same type.



SPECIFICATIONS AND STANDARDS

SAE Viscosity Grade: 5W-30

API Quality Classification: SP/CF

ACEA Quality Classification: C3

Meets the Requirements of:

PSA B71 2290 GM Dexos 2
 OPEL OV 0401547 Renault RN 0700 / RN 0710
 Mercedes-Benz 229.52 BMW LL-04
 Ford WSS-M2C917A Fiat 9.55535-S1
 Renault RN 17 Porsche C30
 VW 502.00 / 505.00

MG Red Shift 5W30 C3 Super Combo	Value
Kinematic Viscosity at 100°C	11.1 mm ² /s
Viscosity Index	156
Total Base Number (TBN)	8.0 mg KOH/g
Pour Point	-35°C
Flash Point	220°C
CCS Viscosity at -25°C	5800 mPa·s
Noack Volatility	11.2 % m/m